column clamp mounts K1C100 🗖 DYNAMIC, SINGLE MONITOR

KONTOUR[™] SERIES







(Shown with Apple® Cinema Display adapter, not included.)

WHAT YOU NEED TO KNOW

INSTALLING THE MONITOR MOUNT The mounting surface thickness must be between 0.5 - 3.25" (12 - 82 mm).

MOUNTING PATTERNS Compatible with 75 x 75 mm and 100 x 100 mm VESA[®] patterns.

QUICK-CONNECT INTERFACE

Easily attach and remove interface from mounting head without removing monitor - no tools necessary!



TECHNICAL DRAWINGS RECOMMENDED ACCESSORY Extension Min 2.13" (54 mm) KRA204 Column Clamp Max 21.7" (551 mm) Grommet Accessory Pitch Tension Adjust Height Min 9.11" (231 mm) Max 32.9" (835 mm) ٠ ۲ -300" 1.5″ <→ (76.2 mm) (38 mm)

For a complete list of monitor mount accessories see page 121.

FEATURES

HEAVY DUTY DESIGN Sleek, solidly constructed forged

aluminum arms.

ULTIMATE FLEXIBILITY Dynamic height adjustment using gas-spring technology with additional adjustment along the column. Ideal for sit-stand applications.

FAST INSTALLATION **F**

Simple 3-step installation and integrated quick-connect interface for easy mounting and maintenance.

CABLE MANAGEMENT

Tool-free cable management covers for a clean, professional look.



CENTRIS" EXTREME TILT PATENTED FEATURE

Tilts -75°/+10° for an ultimate ergonomic solution.

SPECIFICATIONS

Depth from Back of Desk	2.13" (54 mm)
Max. Extension	21.7" (551 mm)
Tilt	-75° / +10°
Height Assist (Column +Arm)	20.8" (528 mm)
Weight Capacity	5 - 25 lbs (2.3 - 11.3 kg)
Colors	Black, Silver





CALL

FAX