# COLUMN CLAMP MOUNTS K1C200 DYNAMIC, DUAL MONITOR

## KONTOUR<sup>™</sup> SERIES

## FEATURES

#### HEAVY DUTY DESIGN Sleek, solidly constructed forged

aluminum arms.

## ULTIMATE FLEXIBILITY

Dynamic height adjustment using gas-spring technology with additional adjustment along the column. Ideal for sit-stand applications.

## FAST INSTALLATION

5

5

Simple 3-step installation and integrated quick-connect interface for easy mounting and maintenance.

## CABLE MANAGEMENT

Tool-free cable management covers for a clean, professional look.

## CENTRIS" EXTREME TILT

PATENTED FEATURE Tilts -75°/+10° for an ultimate ergonomic solution.

SPECIFICATIONS

2.13" (54 mm)

21.7" (551 mm)

20.8" (528 mm)

5 - 25 lbs (2.3 - 11.3 kg)

-75° / +10°

Black, Silver



(Shown with Apple® Cinema Display adapter, not included.)

## WHAT YOU NEED TO KNOW

#### INSTALLING THE MONITOR MOUNT The mounting surface thickness must be between 0.5 - 3.25" (12 - 82 mm).

MOUNTING PATTERNS Compatible with 75 x 75 mm and 100 x 100 mm VESA<sup>®</sup> patterns.

#### **OTHER PRODUCT OPTIONS**



#### K1C250

Dynamic Column Clamp Single Arm Mount, **Dual Monitor** 

\* Per monitor

Colors

Depth from

Tilt

Back of Desk


Max. Extension


Height Assist

(Column + Arm)

Weight Capacity\*

## TECHNICAL DRAWINGS





For a complete list of monitor mount accessories see page 121.





